

# SIGN PRO MAGNETIC CARE GUIDE

## TAKING CARE OF YOUR MAGNETS

Congratulations on your magnet purchase!

Your magnets were produced with high-quality inks and vinyls.

To extend the life of your magnets please follow the care instructions below:

### PREPARATION

- Prepare the surface of the vehicle and the black magnetic side of the sign by cleaning, drying, and waxing before application.

### INSTALLATION

- The magnetic sign should have 100% full contact with a flat steel surface.
- Make contact with one edge first and gently let the full sign rest on the metal surface, removing all air pockets.
- For re-alignment, remove the full sign and start over. Do not pull the magnetic sign to straighten as this may stretch and disfigure it.
- The magnetic sign should be at room temperature when applied to a steel surface. The temperature of the surface of the vehicle is unimportant; however, the sign itself should be at least 60 degrees Fahrenheit for installation.
- Do not apply magnetic over molding, nuts, bolts, pin striping, air vents or rivets.
- Do not apply magnetic over newly painted surfaces. (allow 3 months for paint to cure)
- Magnetic will not stay over patched surfaces.
- Do not use over simulated wood finishes. (veneer finishes on vehicles)

### MAINTENANCE

- Remove magnet at least once per day and clean both the magnetic & steel surface of the vehicle.
- Wipe dry both the magnet and vehicle.
- Use a mild detergent in warm water to clean the vinyl surface of the magnet.
- On rainy or humid days, remove the magnetic signs.
- Keep a good coat of wax on the steel surface.
- Do not lay magnetic signs on pavement or concrete, as debris may adhere to surface, causing potential damage to your vehicle.

### STORAGE

- For best results, store magnetic pieces flat or in rolls. When storing in rolls, wrap coated surface on the outside to avoid the possibility of wrinkles.
- Make sure the inside diameter of the roll is no less than 3"